





LED UNDER WATER LIGHT 25W - SERIES B
PRODUCT OUTDOOR



LED UNDER WATER LIGHT 25W

02

SPECCIFICATION



SPECCIFICATION


- Order Code: UB025, UB025RGBW
- Input Voltage: 24VDC
- Dimension: Ø84xL155xH145 mm
- Chip LED: CREE
- Power consumption: 25W
- Luminous Flux: 2250lm at 3000K, 25W, CRI>90, 36°
- Material: Stainless steel
- Efficiency: 90%
- Environment temperature: from -30° to 60°C
- Color: 3000K, 4000K, 5000K, RGBW
- CRI: >90
- Beam angle: 12° 15° 24° 36° 50°
- IP Rating: IP68
- Life time: 50.000 hour
- Control: ON/OFF
- Standards:
 - + RoHS; EMC protection
 - + IEC 62031LED
 - + IEC 60598 Luminaires



LED UNDER WATER LIGHT 25W

TECHNICAL DETAILS

TECHNICAL DETAILS




Connector IP68





Lens Clear



Legace Reflector



DIMENSIONS




LED UNDER WATER LIGHT 25W


04

SPECIFICATION


PHOTOMETRIC CURVE




BEAM 36° AMPLITUDE DIAGRAM




INSTALLATION



OPTICS




CONNECTOR IP68



LED UNDER WATER LIGHT 25W

05


POWER SUPPLIES - INPUT VOTAGE



LED UNDER WATER LIGHT 25W

06


DIAGRAM CONNECTOR - DMX PROTOCOL - 4 CORE & DECODER



LED UNDER WATER LIGHT 25W

07

DIAGRAM CONNECTOR - DMX PROTOCOL - 5 CORE



LED UNDER WATER LIGHT 25W - Applications

08




OUTDOOR



LANDSCAPE



HOTEL/RESTAURANT



LED UNDER WATER LIGHT 25W - Applications





THANKS FOR YOUR
ATTENTION